CARE & MAINTENANCE

Surfaces should be cleaned with a soft cloth and warm soapy water. Rinse and dry after cleaning. Under no circumstances should abrasive or acid based cleaning products be used.

WARRANTY

This basin is warranted to be free from manufacturing defects for a period of: Lifetime, stainless steel bowl Pop-up waste, 1 year, parts and labour.

This warranty does not cover against normal wear and will be voided if the product is misused or not installed in accordance with these instructions.



Scratching during use does not constitute a product or manufacturing fault.

In the event this product is rendered obsolete and a replacement product is required, Oliveri Solutions Pty Ltd reserves the right to supply a product of equal substitution at their discretion.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be acceptable quality and the failure does not amount to a major failure.

For full warranty information, visit: https://oliveri.com.au/service-and-warranty

SINK SERVICE

If the basin requires servicing, please contact your installer (preferably the one who installed it). If the installer is satisfied that the problem is not due to poor installation, contact Oliveri's nominated **Warranty Service Agent**. For details visit:

https://oliveri.com.au/service-and-warranty

All warranty claims must be directed to our Warranty Service Agent. If the Warranty Service Agent finds that the basin is not faulty, they reserve the right to pass on any callout fee to the householder.

oliveri.com.au

Milan



MI71

Installation Instructions

Round Stainless Steel Counter Top Basin



THIS BASIN MUST BE INSTALLED BY A LICENSED PLUMBER IN ACCORDANCE WITH LOCAL REGULATIONS.

INSTALLATION INSTRUCTIONS FOR COUNTER TOP BASIN

Remove product from packaging:

Check the product for damage, if the product is damaged return to store of purchase. Check the product is complete with all components required to install.

This product is to only be installed by a licensed plumber, failing to do so will void the warranty.

This product is to be installed as per Australian Standard and local authority requirements.

Basin installation:

- 1. Determine where on the bench top the basin is to be installed.
- 2. Place the basin in position and check to ensure the basin waste outlet position does not interfere with drawers, internal walls or waste connection pipe work.

NOTE: We recommend installing the basin so the Oliveri logo is positioned towards the back of the bench, and/or under the tap.

- 3. Mark the waste hole position on the bench top. Using a suitable cutting devise based on bench top material, cut a hole in the bench top large enough to accommodate the recess on the bottom of the basin and the waste being used (hole diameter 80 - 92mm).
- 4. Fit waste to basin as per waste installation instruction document.
- 5. Run a bead of neutral cure silicone around the underside edge of the basin.
- 6. Fit basin to bench top and remove any excess silicone. Allow silicone to set before proceeding with waste pipe installation.

